

HONDA

CBR 600RR my 13/18

(PC40) (no abs)

page 1/2

product	code	description
Steering damper kit	SD.H225R	SDR (stock)
Monoshock (R-P)	MH229.1KD	M46KD std
Monoshock (C-R-L-P)	MH229.07K	M46K std
Monoshock (C-R-L-HP)	MH229.07P	M46K+P1 flex-hydraulic spring preload
Monoshock (CH-CL-R-L-HP)	MH229.07R	M46R Racing (P1 hydraulic unit)
Fork kit (fork type Showa BPF)	FH232RK-BP1	FRK Hydraulic kit (step1)
Fork kit (fork type Showa BPF)	FH232RK-BP2	FRK Hydraulic kit (step2)
Fork kit (C-R-P) (fork type Showa BPF)	F25H232R	F25R Hydraulic Cartridge kit
Fork kit (C-R-P) (fork type Showa BPF)	F25H2232SA	F25SA Sealed Hydraulic Cartridge kit



M46R

Dark Series on demand



M46K



M46KD




High speed
Low speed
Compression
adjustment



Compression
adjustment



Flex-hydraulic
spring preload



Rebound
adjustment



Length
adjustment



CH = HighSpeed Compression adj. / regolazione Compressione AV
CL = LowSpeed Compression adj. / regolazione Compressione BV
C = Compression adjustment / regolazione Compressione
R = Rebound adjustment / regolazione Estensione
L = Length adjustment / regolazione Interasse
P = spring Preload / precarico molla
HP = hydraulic spring éreload adj. / precarico molla idraulico

HONDA

CBR 600RR my 13/18

(PC40) (no abs)

page 2/2

F25SA Sealed cartridge asymmetric system



Rebound unit
(range: 38 clicks)



Preload unit
(range: 15 mm)

Compression unit
(range: 38 clicks)



on demand
the technopolymer fork cap tools

T21 fork cap tool 36 (8 sides)



T22 fork cap tool 28 (6 sides)

FRK-BP step 1



F25R Quad-valve symmetric system



Rebound unit
(range: 38 clicks)

Preload unit
(range: 15 mm)



Compression unit
(range: 38 clicks)



SD-R



FRK-BP step 2

