

MV AGUSTA F3 675 my 12/19 (no abs)

| product | code | description |
|--|------------|---|
| Steering damper kit | SD.M404K | SDK |
| Steering damper kit | SD.M404R | SDR |
| Monoshock (C-R-L-P) | MM403.05K | M46K std |
| Monoshock (C-R-L-HP) | MM403.05IS | M46K+IS hydraulic spring preload |
| Monoshock (CH-CL-R-L-HP) | MM403.05R | M46R Racing (IS preload unit) |
| Fork kit (C-R-P) (fork type Marzocchi) | F20M403K | F20K "quad valve" Hydraulic Cartridge kit |
| Fork kit (C-R-P) (fork type Marzocchi) | F25M403R | F25R "quad valve" Hydraulic Cartridge kit |
| Fork kit (C-R-P) (fork type Marzocchi) | F25M403SA | F25SA Sealed Hydraulic Cartridge kit |



M46R

on demand **Dark Series**



M46K



High speed
Low speed
Compression
adjustment



Compression
adjustment



IS Hydraulic
spring
preload unit



Rebound
adjustment



Length
adjustment



CH = HighSpeed Compression adj. / regolazione Compressione AV
CL = LowSpeed Compression adj. / regolazione Compressione BV
C = Compression adj. / regolazione Compressione
R = Rrebound adj. / regolazione Estensione
L = Length adj. / regolazione Interasse
P = spring Preload by ring / precarico molla standard
HP = hydraulic spring Preload / Precarico molla idraulico

MV AGUSTA F3 675 my 12/19 (no abs)



Sealed asymmetric system



Rebound unit
(range: 38 clicks)



Preload unit
(range: 15 mm)

Compression unit
(range: 38 clicks)

F25SA fork kit

on demand
the technopolymer fork cap tools

T21 fork cap tool 36 (8 sides)



T22 fork cap tool 28 (6 sides)

F20K fork kit



Quad-valve asymmetric system



Compression unit
(range: 38 clicks)

Preload unit
(range: 15 mm)



Rebound unit
(range: 38 clicks)

F25R fork kit

Quad-valve asymmetric system



Compression unit
(range: 38 clicks)

Preload unit
(range: 15 mm)



Rebound unit
(range: 38 clicks)



SD-R

SD-K

